

Technical Specification : Stand Alone Solar Street Light			
Luminary	40W LED Luminary	50W LED Luminary	60W LED Luminary
General Specification			
Application & Operation with High Efficiency	Solar Street Light with Dusk & Dawn automation ,Outdoor application with boost converter with constant current & constant Voltage ,high sensitive indication in battery low & battery over voltage,all protection required for load and battery side i.e. short circuit protection,Reverse polarity protection,No load protection.		
Solar Panel Watt (Max) & Charging Profile	Solar PV Module 150W, Constant current & constant Voltage Charging, 10A Max Current		
Recommended Solar Panel (as per MNRE)	225 Watt	300 Watt	325Watt
Battery Type (Recommended size)	Tubular Lead Acid 100Ah-150Ah		
Dimmability	33% Dimming as per MNRE specifcation OR it can be changed as per customer requirement.		
Qty of LED Chips (Pcs)	18 - 3W	24 - 3W	24 - 3W
Operating Voltage & Current (approx.)	12v,3333mA	12v,4166mA	12v,5000mA
Lithium Battery Capacity (1Day - 1.5 Day)	Li-ion 11.1V/39.6AH	Li-ion 11.1V/49.4AH	Li-ion 11.1V/59.8AH
Recommended Solar Panel (with Lithium battery)	100Wp	150Wp	
Charge Controller Type	МРРТ		
Load & Charging Efficiency	>90%		
LED Lumens/Wp	160 - 165 Lumens /Wp		
LED Temperature	5500°K-6500°K		
Weight	Techno Big (2.3Kg)		
Dimensions	435 (L) x 405 (W) x 445 (H)		
Standard Packing	Techno Big (10pcs)		

 $NOTE:-For\ Lithium\ Battery\ Operation\ ,\ Light\ will\ glow\ in\ full\ bright\ mode\ for\ first\ 4Hrs.\ After\ 4Hrs.\ Light\ will\ Dim\ to\ 33\%\ power\ for\ rest\ Hrs.$